

# Safety Data Sheet

## Luxatemp Automix Plus

Product code: 110368, 110400-110404, 110406 (1300\_GHS)

Page 1 of 5

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Luxatemp Automix Plus

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

**Company Name:** DMG AMERICA LLC  
**Address:** 242 South Dean Street  
**City, State, Zip Code:** Englewood, NJ. 07631  
**Telephone:** (800) 662-6383  
**email address:** [Info@dmg-america.com](mailto:Info@dmg-america.com)  
**Website:** [www.dmg-america.com](http://www.dmg-america.com)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Indications of danger: Xi - Irritant  
R phrases:  
Irritating to eyes, respiratory system and skin.  
May cause sensitisation by skin contact.

#### **GHS classification**

Hazard Statements:  
May cause respiratory irritation.  
Causes serious eye irritation.  
Causes skin irritation.  
May cause an allergic skin reaction.

#### 2.2. Label elements

Signal word: Warning  
Pictograms: GHS07



#### **Hazard statements**

H335 May cause respiratory irritation.  
H319 Causes serious eye irritation.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.

#### **Precautionary statements**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.

#### 2.3. Other hazards

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

# Safety Data Sheet

## Luxatemp Automix Plus

Product code: 110368, 110400-110404, 110406 (1300\_GHS)

Page 2 of 5

### Chemical characterization

chemical characterization (preparation): Acrylate.-resin.

### Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
	Dimethacrylate Resin	35-45 %
41637-38-1	Xi - Irritant R36/37/38-43	

Full text of R and H phrases: see Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### After inhalation

Exposition vermeiden. Provide fresh air. Move victim to fresh air. Put victim at rest and keep warm.

#### After contact with skin

After contact with skin, wash immediately with: Water and soap.

#### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

#### After ingestion

Consult physician.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO<sub>2</sub>).

#### Extinguishing media which must not be used for safety reasons

High power water jet.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.

### 6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

### 6.3. Methods and material for containment and cleaning up

Collect mechanically. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

# Safety Data Sheet

## Luxatemp Automix Plus

Product code: 110368, 110400-110404, 110406 (1300\_GHS)

Page 3 of 5

Store only in original container.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### 8.2. Exposure controls



#### **Protective and hygiene measures**

When using do not eat or drink.

#### **Respiratory protection**

The following must be prevented: inhalation.

#### **Hand protection**

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

#### **Eye protection**

Tightly sealed safety glasses.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	characteristic
Odour:	ester

#### **Test method**

pH-Value (at 20 °C):	ca. 7
----------------------	-------

#### **Changes in the physical state**

Boiling point:	>250 °C
----------------	---------

point of decomposition:	200 °C
-------------------------	--------

Flash point:	>150 °C
--------------	---------

Ignition temperature:	>380 °C
-----------------------	---------

Vapour pressure: (at 20 °C)	1 hPa
--------------------------------	-------

Density:	1,5 g/cm <sup>3</sup>
----------	-----------------------

Water solubility:	10 g/L
-------------------	--------

Vapour density:	1
-----------------	---

### SECTION 10: Stability and reactivity

#### 10.4. Conditions to avoid

heat. Light.

Decomposition takes place from temperatures above: 200 °C

Decomposition under formation of: Acrylate.

#### 10.5. Incompatible materials

radical former. Keep away from strong acids, leachates, heavy metal salts and reducing materials.

#### 10.6. Hazardous decomposition products

Can be released in case of fire: Gas / vapours, irritant. (Acrylate., pungent). nitrogen oxides (NOx).

# Safety Data Sheet

## Luxatemp Automix Plus

Product code: 110368, 110400-110404, 110406 (1300\_GHS)

Page 4 of 5

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity

LD50: Rat. 5000 mg/kg

##### Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

Irritant effect on the eye:

##### Additional information on tests

Contains Methacrylic esters.: May produce an allergic reaction.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Acute fish toxicity LC50: >360 mg/l/48h

#### 12.2. Persistence and degradability

Preparation not tested.

#### Further information

Do not empty into drains or the aquatic environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Advice on disposal

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Paste: Carry out a burning of hazardous waste according to official regulations.

##### Waste disposal number of waste from residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing dangerous substances  
Classified as hazardous waste.

### SECTION 14: Transport information

#### Other applicable information

Not a hazardous material with respect to these transportation regulations.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### National regulatory information

### SECTION 16: Other information

#### Full text of R phrases referred to under Sections 2 and 3

36/37/38 Irritating to eyes, respiratory system and skin.  
43 May cause sensitisation by skin contact.

#### Full text of H statements referred to under Sections 2 and 3

H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.

# Safety Data Sheet

## Luxatemp Automix Plus

Product code: 110368, 110400-110404, 110406 (1300\_GHS)

Page 5 of 5

H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.

---

*The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.*