

NAME OF PRODUCT: COPALINER® Cavity Varnish and Sealant **SDS DATE:** 06/19/2014

SECTION 1: IDENTIFICATION

PRODUCT NAME: **COPALINER Cavity Varnish and Sealant**

PRODUCT CODES: 0921525, 0921526, 0921527

IDENTIFIED USES: Dentistry **USES ADVISED AGAINST:** Non-dental use

MANUFACTURER: Harry J. Bosworth Company

ADDRESS: 7227 North Hamlin Avenue, Skokie, Illinois 60076-3999, USA

TELEPHONE: 847-679-3400 FAX: 847-679-2080 hjbinfo@bosworth.com EMAIL:

EMERGENCY PHONE: 800-535-5053 (US and Canada)

352-323-3500 (International)

SECTION 2: HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable liquids (Category 2)

Acute toxicity, Oral (Category 4) Eye irritation (Category 2A)

Specific target organ toxicity - single exposure (Category 3), Central nervous system

FILE NO.: SDS525

LABELING: FDA regulated device - exempt from Regulation (US) 29 CFR 1910.1200.

PICTOGRAM:



SIGNAL WORD: Danger

PRECAUTIONARY STATEMENTS:

HAZARD STATEMENTS: H225 Highly flammable liquid and vapor.

H302 Harmful if swallowed. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P210

P234 Keep only in original container. P235+P410 Keep cool. Protect from sunlight.

P240 Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment. P241

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling. P264

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse

skin with water/ shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Call a POISON CENTER or doctor/ physician if you feel unwell. P312 P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide P370+P378

for extinction.

Collect spillage. P391 P402 Store in a dry place.

Store in a well-ventilated place. Keep container tightly closed. P403+P233 P501 Dispose of contents/container to an approved waste disposal plant.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

PREPARED BY: SS PAGE 1 OF 4



NAME OF PRODUCT: COPALINER® Cavity Varnish and Sealant

COMPONENT	CAS NO.	%WT	OSHA PEL - TWA	ACGIH TLV - TWA	CLASSIFICATION
Diethyl Ether	60-29-7	40-50	400 ppm	400 ppm	Flam. Liq. 1; Acute Tox. 4;
					STOT SE 3; H224, H302, H336
2-Propanol	67-63-0	40-50	400 ppm	200 ppm	Flam. Liq. 2; Eye Irrit. 2A; STOT
					SE 3; H225, H319, H336
Ethanol	64-17-5	1-5	1000 ppm	1000 ppm	Flam. Liq. 2; H225

For full text of H-statements mentioned in this section, see section 16.

SECTION 4: FIRST-AID MEASURES

INHALATION: Move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

SKIN: Wash off with soap and plenty of water. Consult a physician.

EYE: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water.

Consult a physician.

SECTION 5: FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon.

SPECIAL HAZARDS: Vapors are heavier than air and may travel to ignition source.

ADVICE FOR FIREFIGHTERS: Fight fires from safe distance or protected areas. Cool containers of material exposed to heat with cold water

spray. Wear self contained breathing apparatus for firefighting if necessary.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation.

Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form

FILE NO.: SDS525

SDS DATE: 06/19/2014

explosive concentrations. Vapors can accumulate in low areas.

ENVIRONMENTAL PRECAUTIONS: Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

CONTAINMENT AND CLEANUP: Soak up with inert absorbent material and collect with an electrically protected vacuum cleaner or by wet-

brushing. Place in suitable, closed container for disposal according to official regulations.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: Product is intended for dental use only. Handling of this product should be by trained dental healthcare

professionals only. Observe normal care for working with chemicals. Avoid contact with the eyes and skin. Avoid inhalation of vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge. Keep away from foodstuffs, beverages and animal feed.

CONDITIONS FOR SAFE STORAGE: Store only in the original package. Keep container tightly sealed in a dry and well-ventilated place. Protect

from heat and direct sunlight. Store away from food and beverages.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Handle in accordance with good industrial hygiene and safety practice. Use with adequate general or local

exhaust ventilation to maintain exposure levels below the occupational exposure limits. Local exhaust ventilation is preferred since it prevents contamination dispersion into the work area by controlling it at its source. Provide eyewash and safety shower if contact or splash hazard exists. Wash hands before breaks and

at the end of work. Safety glasses.

SKIN PROTECTION: Glove material impermeable and resistant to the product.

BODY PROTECTION: Protective work clothing.

RESPIRATORY PROTECTION: NIOSH (US) or CEN (EU) approved respirators and components.

ENVIRONMENTAL EXPOSURE: Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE/COLOR: Clear, colorless to straw yellow liquid

ODOR: Sweet

EYE/FACE PROTECTION:

PREPARED BY: SS PAGE 2 OF 4



NAME OF PRODUCT: COPALINER® Cavity Varnish and Sealant

INITIAL BOILING POINT: 114.8°F (46°C)

FLASH POINT: -40°F (-40°C) (diethyl ether)
EVAPORATION RATE (BuAc = 1.0): 37.5 (diethyl ether)
UPPER FLAMMABILITY LIMIT: 48 (diethyl ether)
LOWER FLAMMABILITY LIMIT: 1.8 (diethyl ether)

VAPOR PRESSURE: 422 mmHg at 68°F (20°C) (diethyl ether)

VAPOR DENSITY (AIR=1.0): 2.56 (diethyl ether)
RELATIVE DENSITY (H2O=1.0): 0.77 g/cm³
WATER SOLUBILITY: Slightly soluble

SECTION 10: STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable under recommended storage conditions. **HAZARDOUS REACTIONS:** Vapors may form explosive mixture with air.

CONDITIONS TO AVOID: Heat, flames, sparks. Extremes of temperature and direct sunlight.

INCOMPATIBLE MATERIALS: Oxidizing agents, acid anhydrides, aluminum, halogenated compounds, acids.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon.

SECTION 11: TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS: EYES: May cause eye irritation with redness, tearing and stinging. Prolonged exposure to high concentration

of vapor can cause eye damage.

SKIN: May cause skin irritation with redness, swelling and itching. Repeated or prolonged contact may cause

FILE NO.: SDS525

SDS DATE: 06/19/2014

drying, defatting of the skin and dermatitis.

<u>INGESTION:</u> May cause mucous membrane and gastrointestinal irritation with nausea, vomiting and diarrhea. May cause nervous system depression with symptoms of headache, dizziness, nausea, vomiting, weakness,

fatigue, confusion, and unconsciousness. Ingestion of one or two ounces may be fatal.

<u>INHALATION:</u> May cause mucous membrane and respiratory irritation and central nervous system depression

with symptoms of headache, dizziness, drowsiness, nausea, vomiting, and unconsciousness. High vapor concentrations may cause burning sensation of the nose and throat and watering of the eyes.

CARCINOGENICITY: OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or possible carcinogen by OSHA.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or

anticipated carcinogen by NTP.

IARC: 2-Propanol is identified as not classifiable as to its carcinogenicity to humans by IARC.

SECTION 12: ECOLOGICAL INFORMATION

ADVERSE EFFECTS: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: DISPOSAL CONSIDERATIONS

PRODUCT: Contact a licensed professional waste disposal service to dispose of this material. Burn in a chemical

incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Disposal must be made

according to official regulations.

CONTAMINATED PACKAGING: Dispose of as unused product.

SECTION 14: TRANSPORT INFORMATION

UN NUMBER: UN1993

PROPER SHIPPING NAME: Flammable liquid, n.o.s. (contains Diethyl Ether and Isopropyl Alcohol)

HAZARD CLASS: 3
PACKING GROUP: II

LABEL STATEMENT: Flammable Liquid

SECTION 15: REGULATORY INFORMATION

PREPARED BY: SS PAGE 3 OF 4



NAME OF PRODUCT: COPALINER® Cavity Varnish and Sealant

US FEDERAL REGULATIONS

TSCA: This product is an FDA regulated device and not subject to TSCA regulations.

CERCLA: This product is an FDA regulated device and not subject to reporting requirements. There may be specific

reporting requirements at the local, regional, or state level.

SARA 313 TOXIC CHEMICALS: The following components are subject to reporting levels established by SARA Title III, Section 313 (40 CFR

372): 2-Propanol, CAS NO. 67-63-0.

SARA 311/312 HAZARDS: This product is an FDA regulated device and not subject to reporting requirements.

US STATE REGULATIONS

CALIFORNIA PROPOSITION 65: This product may contain a chemical known to the State of California to cause cancer and/or reproductive

toxicity.

INTERNATIONAL REGULATIONS

CANADIAN ENVIRONMENTAL

PROTECTION ACT:

This product is a medical device and not subject to chemical notification requirements.

FILE NO.: SDS525

SDS DATE: 06/19/2014

EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES

(EINECS):

This product is a medical device and not subject to chemical notification requirements.

SECTION 16: OTHER INFORMATION

FULL TEXT OF H STATEMENTS REFERRED TO UNDER SECTION 3

Acute Tox. Acute toxicity
Eye Irrit. Eye irritation
Flam. Liq. Flammable liquids

H224 Extremely flammable liquid and vapor.
H225 Highly flammable liquid and vapor.

H302 Harmful if swallowed.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

STOT SE Specific target organ toxicity – single exposure

NFPA RATING

Health Hazard 2
Fire Hazard 4
Reactivity Hazard 1

PREPARATION INFORMATION: This SDS was prepared in accordance with the requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200) and is to be used only for this product.

DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, The Harry J. Bosworth Company does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

PREPARED BY: SS PAGE 4 OF 4