

Valueklave™1730

Valueklave 1730





Speed, Quality & Value

- Fast cycle time, 11 minutes from a hot start (Standard Unwrapped Cycle Time)
- Efficent drying cycle for wrapped instruments
- Contemporary design with easy to read panel
- Economically priced a compact size

Valueklave™1730

The Valueklave[™]1730 will satisfy all of your basic sterilization needs at an economical price. High speed and reliability are built into every Valueklave[™] 1730.



Feati	IL62.

- Fast Cycle Time. 11 minutes from a hot start* (Standard Unwrapped Cycle time).
- Automatic shut off at the end of both the sterilization and dry cycles.
- A long life electro polished chamber and door.
- Double safety locking device prevents door from opening while chamber is pressurized.
- Overheat cutoff prevents burnout of heating elements in case of insufficient water in the chamber.
- Drain valve is located on the front, allowing for quick and easy draining of water reservoir.
- Dual safety thermostat to protect against overheating.
- International certifications.

Valueklave™ 1730 Specification	
Chamber Dimensions	7"x13"
0 x L in (mm)	(170 X 340)
Volume	2 gal/7.5 L
Overall Dimensions	17.9"x 17.4 "x 12"
DxWxH in (mm)	(455 x 440 x 305)
Standard Cassettes	2 half
Tray Dimensions	11.6"x 4.7 "x 0.8"
DxWxH in (mm)	(295 x 120 x 20)
No. of Trays	3
Standard Unwrapped	Cold: 16 min
Cycle Time	Hot: 11 min
Voltage (V)	120
Freq. (Hz)	50/60
Power (W)	1350
Curret (A)	11
Shipping Weight lbs (kg)	55 (25)



*Come up time, sterilization exposure and exhaust



Clean&Simple™ Ultrasonic Cleaners and Tablets



Steam Distiller



Chamber Brite Autoclave Cleaner













